



DÖKÜM GÖVDELİ DIŞLI POMPALAR




ISO SERİSİ				
KOD	İletim Hacmi		Ç.Basınç (bar)	Max. Hız d/dk
	cm ³	lt (1500 d/dk)		
ISO EHASS-17(L,R,BD)	17.2	25.8	300	2600
ISO EHASS-27(L,R,BD)	27.3	40.95	290	2600
ISO EHASS-34(L,R,BD)	33.8	50.7	285	2300
ISO EHASS-43(L,R,BD)	43.8	65.7	280	2100
ISO EHASS-51(L,R,BD)	51.73	77.59	230	2100
ISO EHASS-61(L,R,BD)	61.95	92.92	225	2000
ISO EHASS-82(L,R,BD)	82.13	123.19	200	1700
ISO EHASS-100(L,R,BD)	102.5	153.75	190	1600
ISO EHASS-125(L,R,BD)	127.5	191.25	170	1600

L:Left/Sol, R:Right/Sağ, BD: Bidirectional/Çift dönüşlü



UNI SERİSİ				
KOD	İletim Hacmi		Ç. Basınç (bar)	Max. Hız d/dk
	cm ³	lt (1500 dev/dk)		
UNI EHASS-17(L,R,BD)	17.2	25.8	300	2600
UNIEHASS-27(L,R,BD) (L,R,BD)	27.3	40.95	290	2600
UNI EHASS-34(L,R,BD)	33.8	50.7	285	2300
UNI EHASS-43(L,R,BD)	43.8	65.7	280	2100
UNI EHASS-51(L,R,BD)	51.73	77.59	230	2100
UNI EHASS-61(L,R,BD)	61.95	92.92	225	2000
UNI EHASS-82(L,R,BD)	82.13	123.19	200	1700
UNI EHASS-100(L,R,BD)	102.5	153.75	190	1600
UNI EHASS-125(L,R,BD)	127.5	191.25	170	1600



ASAE ISO SERİSİ				
KOD	İletim Hacmi		Ç.Basınç (bar)	Max. Hız d/dk
	cm ³	lt (1500 dev/dk)		
ASAE ISO R(L) EHASS-17	17.2	25.8	300	2600
ASAE ISO R(L) EHASS-27	27.3	40.95	290	2600
ASAE ISO R(L) EHASS-34	33.8	50.7	285	2300
ASAE ISO R(L) EHASS-43	43.8	65.7	280	2100
ASAE ISO R(L) EHASS-51	51.73	77.59	230	2100
ASAE ISO R(L) EHASS-61	61.95	92.92	225	2000
ASAE ISO R(L) EHASS-82	82.13	123.19	200	1700
ASAE ISO R(L) EHASS-100	102.5	153.75	190	1600
ASAE ISO R(L) EHASS-125	127.5	191.25	170	1600