

## HİDROLİK SOĞUTUCULAR



### ELEKTRİK MOTORLU YAĞ SOĞUTUCULARI

Kod	M.Hacimsel Debi lt/dk	Kapasite Kcal/h	Max. Basınç Bar	Termostat	Motor Tipi
ES2007	20 (CNC)	1100	20	60/48 °C	24 V DC
ES2007	20	1000	20	60/48 °C	220 V AC
ES 2008K	60	2500	24	60/48 °C	12 V DC
ES 2008K	60	2500	24	60/48 °C	24 V DC
ES 2008K	60	2500	24	60/48 °C	220 V AC
ES 2012K	100	6500	24	60/48 °C	12 V DC
ES 2012K	100	6500	24	60/48 °C	24 V DC
ES 2012K	100	6500	24	60/48 °C	220 V AC
ES 2028K	150	15000	24	60/48 °C	12 V DC
ES 2028K	150	15000	24	60/48 °C	24 V DC
ES 2028K	150	15000	24	60/48 °C	220 V AC
ES 2080K	250	32000	24	60/48 °C	12 V DC
ES 2080K	250	32000	24	60/48 °C	24 V DC
ES 2080K	250	32000	24	60/48 °C	220 V AC

\*Fan Müşürleri (Termostat) Fiyata Dahildir.



### SULU SOĞUTUCULAR

Kod	M.Hacimsel Debi lt/dk	Kapasite Kcal/h	Max. Basınç Bar	Yağ Giriş Ölçüsü	Su Giriş Ölçüsü
EOR-60	60	7000	10	3/4"	3/4"
EOR-100	100	12.000	10	3/4"	3/4"
EOR-150	150	19.000	10	1-1/4"	1"
EOR-250	250	30.000	10	1-1/4"	1"
EOR-350	350	40.000	10	1-1/4"	1"
EOR-600	600	62.000	10	2"	1-1/4"
EOR-800	800	90000	10	2"	1-1/4"

\*Yağ Girişleri Üstten, Su Girişleri Yandandır